



Symbol of Perfection

**Attachment models • series SZA**



SZA-850

The Solo-Swing is a swinging mowing disk, driven by a hydraulic motor. It's simple but robust construction allows to automatically mow around trees, fences, posts etc.

The SZA is an attachment model which can be supplied with mounting brackets to be fitted to a rotary mower or a flail mower.

Available in 3 cutting widths:  
 SZA-500: 50 cm (1'8")  
 SZA-600: 60 cm (2'0")  
 SZA-850: 85 cm (2'9½")



SZA-600



SZA-600 with optional mounting frame for mini loaders.

All Solo-Swing models have swing-away blades, which are less funarable for obstacles, as standard.

Specifications		SZA-500	SZA-600	SZA-850
Cutting width	cm/inch	50/1'8"	60/2'0"	85/2'9½"
Oil flow requirements	l/min.	30	30	30
Oil pressure requirements (average, depending on kind of work)	bar/psi	±80/1160	±80/1160	±80/1160
Displacement of motor	cc/cu.in.	16/1	16/1	17,9/1,1
Cutting angle		0-15	0-15	0-15
Discharge angle		0-15	0-15	0-15
Tractor hydraulics required		1 x double acting valve, 1 x free flow return	1 x double acting valve, 1 x free flow return	1 x double acting valve, 1 x free flow return
Weight	kg/lbs	75/165	95/210	110/242



Mechanic-hydraulic feeler

For young trees, lighter posts, or when operating on inclines all "Perfect" Solo-Swing model can be provided with a hydraulic feeler mechanism.

Available options:

- Support for mounting on a "Perfect" pasture topper
- Support for mounting on a "Perfect" flail topper
- Mechanic-hydraulic feeler